



NSK LINEAR GUIDES

MINIATURE PU SERIES/PE SERIES

Ideal for semiconductor manufacturing and medical equipment.



SUBSCRIBE TO NSK NEWSLETTER 

SMOOTH MOTION AND UNPRECEDENTED LIGHTNESS

THE ADVANCED NSK MINIATURE LINEAR GUIDES

The new generation PU series/PE series inherit the outstanding lineage of the NSK miniature linear guides LU series/LE series. Improves dynamic friction characteristics and creates smoother motion with reduced noise intensity. The new design supports a wide variety of applications.

FEATURES

1. Motion performance

Optimally designed recirculation components facilitate smooth circulation of steel balls.

2. Lightweight

The ball slide is designed to be approximately 20% lighter than conventional models* by using resin in the recirculation components.

*Miniature LU series/LE series

3. Reduced noise intensity

Resin recirculation components reduce ball to inner wall collision noise.

4. Low particle generation

The new design generates less particles compared to conventional models.

5. Excellent contamination resistance

Compact space between the side of the rails and the inner walls of the ball slide prevents the entrance of foreign matter.

6. High corrosion resistance

Martensite stainless steel is a standard feature that provides excellent corrosion resistance.

7. Easy handling

Design prevents steel balls from dropping out of the ball slide even when the slide is removed from the rail.

8. Long-term maintenance-free

Equipped with NSK K1™ Lubrication unit to extend product life.

9. Fast delivery

Wide selection of interchangeable rails and ball slides for PU/PE Series.

MINIATURE PU
(Interchangeable with LU Series)



WIDE MINIATURE PE
(Interchangeable with LE Series)






PU09TR



PE09TR



PU15

Cutaway View

SMOOTHER MOTION

The resin ball recirculation component creates an optimal configuration, resulting in smoother motion.

Test conditions: Oil lubrication (VG68)
Operating speed: 1 000 mm/min
Load cell rated capacity: 5N




Fig. 1-1 Fluctuations in Dynamic Friction

LOW PARTICLE GENERATION

The PU series/PE series, with resin ball recirculation components, generates less particles than a conventional ball recirculation system.

Test conditions: Grease lubrication (LG2)
Operating speed: 600 mm/min
Stroke: 200 mm




Fig. 1-2 Particle Generation Rate




Fig. 2 Cross Sectional Front View

DEVELOPED FOR PRECISION POSITIONING TABLES INCLUDING SEMICONDUCTOR MANUFACTURING AND MEDICAL DEVICES

REFERENCE NUMBER

Reference numbers will be used as reference before finalizing all specifications. Please specify the reference number, except design serial number, to identify the product when ordering, requesting estimates, or inquiring about specifications from NSK.

PRELOADED ASSEMBLY TYPE

PU	15	0470	AL	K	2	-***	P5	1
SERIES NAME	SIZE	RAIL LENGTH (MM)	BALL SLIDE SHAPE CODE	MATERIAL/SURFACE TREATMENT CODE K: Stainless Steel H: Stainless Steel + surface treatment	NUMBER OF BALL SLIDES PER RAIL	DESIGN SERIAL NUMBER	ACCURACY CODE P4: Super Precision P5: High Precision P6: Precision PN: Normal K4: Super Precision with K1 K5: High Precision with K1 K6: Precision with K1 KN: Normal with K1	PRELOAD CODE 0: Fine Clearance - Z0 1: Slight Preload - Z1

INTERCHANGEABLE TYPE

Reference number for rail and ball slide assembly

PU	15	0470	AL	K	2	-***	PC	T
SERIES NAME	SIZE	RAIL LENGTH (MM)	BALL SLIDE SHAPE CODE	MATERIAL/SURFACE TREATMENT CODE K: Stainless Steel H: Stainless Steel + surface treatment	NUMBER OF BALL SLIDES PER RAIL	DESIGN SERIAL NUMBER	ACCURACY CODE PC: Normal KC: Normal with K1	PRELOAD CODE T: Fine Clearance - ZT

Reference number for ball slide of interchangeable type

PAU	15	AL	S	-	K
SERIES CODE PAU: PU Series Interchangeable Ball Slide PAE: PE Series Interchangeable Ball Slide	SIZE	BALL SLIDE SHAPE CODE	MATERIAL CODE S: Stainless Steel		OPTION CODE K: Equipped with K1

Reference number for rail of interchangeable type

P1U	15	0470	R	K	N	-***	PC	T
SERIES CODE P1U: PU Series Interchangeable Rail P1E: PE Series Interchangeable Rail	SIZE	RAIL LENGTH (MM)	RAIL SHAPE CODE S: PU09-12 R: PU15, PE09, 12 P: PE15	MATERIAL/SURFACE TREATMENT CODE K: Stainless Steel H: Stainless Steel + surface treatment	BUTTING SPECIFICATION N: Non-butting rails L: Butting specification	DESIGN SERIAL NUMBER	ACCURACY CODE PC: Normal	PRELOAD CODE T: Fine Clearance - ZT

* Please consult NSK for butting rail specification.

ACCESSORIES

Plastic Cap for Rail Mounting Hole

Linear Guide Model No.	Rail Mounting Bolt Size	Cap. No. for Rail Mounting Hole
PU09, PU12, PU15, PE09	M3	L45800003-003

ACCURACY STANDARD

We offer the following accuracy grades: Super precision grade P4, High precision grade P5, Precision grade P6, and Normal grade PN for preloaded assembly type, and Normal grade PC for interchangeable type.

Table 1 Tolerance of preloaded assembly

Unit: μm

Characteristics	Accuracy grade	Super precision P4	High precision P5	Precision grade P6	Normal grade PN
Mounting height H		± 10	± 15	± 20	± 40
Variation of H (All ball slides on a set of rails)		5	7	15	25
Mounting width W_2 or W_3		± 15	± 20	± 30	± 50
Variation of W_2 or W_3 (All ball slides on reference rail)		7	10	20	30
Running parallelism of surface C to surface A	Shown in Table 3, Fig. 3, Fig. 4				
Running parallelism of surface D to surface B					

Table 3 Running parallelism of ball slide

Unit: μm

Rail length (mm)		Preloaded assembly type				Interchangeable type
over	to (incl)	P4	P5	P6	PN	PC
	50	2	2	4.5	6	6
50	80	2	3	5	6	6
80	125	2	3.5	5.5	6.5	6.5
125	200	2	4	6	7	7
200	250	2.5	5	7	8	8
250	315	2.5	5	8	9	9
315	400	3	6	9	11	11
400	500	3	6	10	12	12
500	630	3.5	7	12	14	14
630	800	4.5	8	14	16	16
800	1 000	5	9	16	18	18
1 000	1 250	6	10	17	20	20

**Table 2 Tolerance of interchangeable type:
Normal grade PC**

Unit: μm

Characteristics	Accuracy grade	Normal grade
		PC
Mounting height H		± 20
Variation of mounting height H		15 ¹⁾ 30 ²⁾
Mounting width W_2 or W_3		± 20
Variation of mounting width W_2 or W_3		20
Running parallelism of surface C to surface A	Shown in Table 3, Fig. 3, Fig. 4	
Running parallelism of surface D to surface B		

¹⁾ Variation on the same rail

²⁾ Variation on multiple rails




Fig. 3 Assembled Accuracy Mounting width W_2




Fig. 4 Assembled Accuracy Mounting width W_3

PRELOAD AND RIGIDITY

Three options are available: Slight preload (Z1) and Fine clearance (Z0) for matched assembly types, along with interchangeable types of Fine clearance (ZT). Values for preload and rigidity are shown in Tables 4 and 5.

Table 4 Preload and rigidity of preloaded assembly of PU series

	Model No.	Preload (N)	Rigidity (N / μ m)
		Slight preload (Z1)	Slight preload (Z1)
Standard type	PU05TR	0 - 3	17
	PU07AR	0 - 8	22
	PU09TR	0 - 10	30
	PU12TR	0 - 17	33
	PU15AL	0 - 33	45
High-load type	PU09UR	0 - 14	46
	PU12UR	0 - 25	52
	PU15BL	0 - 51	75

Clearance of fine clearance Z0 is 0-3 μ m. Therefore, preload is zero.
Clearance values of the interchangeable types are shown in Tables 6 and 7.

Table 6 Clearance of interchangeable type of PU Series

Unit: μ m		
	Model No.	Fine clearance ZT
Standard type	PU09TR	3 or less
	PU12TR	
	PU15AL	
High-load type	PU09UR	5 or less
	PU12UR	
	PU15BL	

Table 5 Preload and rigidity of preloaded assembly of PE series

	Model No.	Preload (N)	Rigidity (N / μ m)
		Slight preload (Z1)	Slight preload (Z1)
Standard type	PE05AR	0 - 28	45
	PE07TR	0 - 29	46
	PE09TR	0 - 37	61
	PE12AR	0 - 40	63
	PE15AR	0 - 49	66
High-load type	PE09UR	0 - 54	86
	PE12BR	0 - 59	97
	PE15BR	0 - 75	114

Table 7 Clearance of interchangeable type of PE Series

Unit: μ m		
	Model No.	Fine clearance ZT
Standard type	PE09TR	3 or less
	PE12AR	
	PE15AR	
High-load type	PE09UR	5 or less
	PE12BR	
	PE15BR	

SHOULDER HEIGHT H OF THE MOUNTING SURFACE AND CORNER RADIUS R

Figs. 5, 6 and Tables 8, 9 show the shoulder height and corner radius dimensions.




Fig. 5 Shoulder for the rail datum face




Fig. 6 Shoulder for the ball slide datum face

Table 8 Shoulder height H of the mounting surface and corner radius r (PU Series)

Model No.	Corner radius (Maximum)		Shoulder height	
	r_a	r_b	H'	$H''(^{\circ})$
PU05	0.2	0.2	0.7	2.3
PU07	0.2	0.3	1.2	2.5
PU09	0.3	0.3	1.9	2.6
PU12	0.3	0.3	2.5	3.4
PU15	0.3	0.5	3.5	4.4

($^{\circ}$) H'' is the minimum recommended value based on the dimension T in Table 13.

Table 9 Shoulder height H of the mounting surface and corner radius r (PE Series)

Model No.	Corner radius (Maximum)		Shoulder height	
	r_a	r_b	H'	$H''(^{\circ})$
PE05	0.2	0.2	1.1	2.5
PE07	0.2	0.3	1.7	3.0
PE09	0.3	0.3	3.5	2.8
PE12	0.3	0.3	3.5	3.2
PE15	0.3	0.5	3.5	4.1

($^{\circ}$) H'' is the minimum recommended value based on the dimension T in Table 14.

LUBRICATION

Selection of grease: Table 10 shows grease that is suitable for the PU series/PE series. NSK recommends PS2 as the standard grease for our miniature linear guides.

Table 10 Available Greases

Grease code	Thickener	Base oil	Base oil kinematic viscosity mm ² /s (40°C)	Temperature range for use (°C)	Characteristic/Application
PS2	Lithium type	Synthetic oil + Synthetic hydrocarbon oil	15.9	-50 to 110	• For low temperature operation • Suitable for high speed and light load application
LG2	Lithium type	Mineral oil + Synthetic hydrocarbon oil	32.0	-20 to 70	• For clean environment
LGU	Diurea type	Synthetic hydrocarbon oil	95.8	-30 to 120	• For clean environment

Long term maintenance free: NSK K1™ Lubrication unit enables long term maintenance free operation.




Table 11 Dimensions when equipped with NSK K1™ (PU Series)

Unit: mm

	Model No.	Standard ball slide length	Ball slide length equipped with two NSK K1, L	Thickness of NSK K1, V ₁	Thickness of protective cover, V ₂
Standard type	PU05TR	19.4	24.4	2	0.5
	PU07AR	23.4	29.4	2.5	0.5
	PU09TR	30	36.4	2.7	0.5
	PU12TR	35	42	3	0.5
	PU15AL	43	51.2	3.5	0.6
High-load type	PU09UR	41	47.4	2.7	0.5
	PU12UR	48.7	55.7	3	0.5
	PU15BL	61	69.2	3.5	0.6

Table 12 Dimensions when equipped with NSK K1™ (PE Series)

Unit: mm

	Model No.	Standard ball slide length	Ball slide length equipped with two NSK K1, L	Thickness of NSK K1, V ₁	Thickness of protective cover, V ₂
Standard type	PE05AR	24.1	28.9	2	0.4
	PE07TR	31.1	37.1	2.5	0.5
	PE09TR	39.8	46.8	3	0.5
	PE12AR	45	53	3.5	0.5
	PE15AR	56.6	66.2	4	0.8
High-load type	PE09UR	51.2	58.2	3	0.5
	PE12BR	60	68	3.5	0.5
	PE15BR	76	85.6	4	0.8

Ball slide length equipped with NSK K1™ = (Standard ball slide length) + (Thickness of NSK K1™, V₁ × Number of NSK K1™) + (Thickness of the protective cover, V₂ × 2)
Additional NSK K1™ units are available depending on the conditions of use.

CONTAMINATION RESISTANCE

End seal: Installed on both sides of the ball slide are a standard feature.

Bottom seal function: Designed to minimize the clearance between the side faces of rail and the inner walls of the slide, and prevent contamination from entering the ball slide.

APPLICATIONS

- › **Smoother motion and low particle generation**
Liquid crystal manufacturing and printed circuit board manufacturing devices
- › **Lightweight and low particle generation**
Semiconductor manufacturing devices (mounter, die bonder, and exposure device)
- › **Gentler tone and excellent particle resistant features**
Medical machinery and various precision devices

DIMENSIONS

RAIL AND BALL SLIDE ASSEMBLY (PRELOADED TYPE, INTERCHANGEABLE TYPE)




Table 13 Dimensions (PU Series)

Model No.	Interchangeable type	Assembly			Ball slide													Rail		
		Height H	E	W ₂	Width W	Length L	Mounting hole			B ₁	L ₁	J ₁	K	T	Oil hole			Width W ₁	Height H ₁	Pitch F
							B	J	M×Pitch×ℓ						Hole diameter	T ₁	N			
PU05TR	—	6	1.0	3.5	12	19.4	8	—	M2×0.4×1.5	2.0	11.4	5.70	5.0	2.30	Ø0.9	1.5	—	5	3.2	15
PU07AR	—	8	1.5	5.0	17	23.4	12	8	M2×0.4×2.4	2.5	13.3	2.65	6.5	2.45	Ø1.5	1.8	—	7	4.7	15
PU09TR	■	10	2.2	5.5	20	30.0	15	10	M3×0.5×3	2.5	19.6	4.80	7.8	2.60	—	—	—	9	5.5	20
PU09UR	■	10	2.2	5.5	20	41.0	16	16	M3×0.5×3	2.5	30.6	7.30	7.8	2.60	—	—	—	9	5.5	20
PU12TR	■	13	3.0	7.5	27	35.0	20	15	M3×0.5×3.5	3.5	20.4	2.70	10.0	3.40	—	—	—	12	7.5	25
PU12UR	■	13	3.0	7.5	27	48.7	20	20	M3×0.5×3.5	3.5	34.1	7.05	10.0	3.40	—	—	—	12	7.5	25
PU15AL	■	16	4.0	8.5	32	43.0	25	20	M3×0.5×5	3.5	26.2	3.10	12.0	4.40	Ø3 (°1)	3.2	(3.6)	15	9.5	40
PU15BL	■	16	4.0	8.5	32	61.0	25	25	M3×0.5×5	3.5	44.2	9.60	12.0	4.40	Ø3 (°1)	3.2	(3.6)	15	9.5	40

■: Interchangeable type is available.

(°1) Drive-In grease fitting for Ø3 is available to PU15.

(2) Basic dynamic load rating is a load that allows for a 50-km rating fatigue life and is a vertical and constant load on the ball slide mounting surface. To convert C to C₁₀₀ for a 100-km rating fatigue life, divide C by 1.26.

Table 14 Dimensions (PE Series)

Model No.	Interchangeable type	Assembly			Ball slide													Rail		
		Height H	E	W ₂	Width W	Length L	Mounting hole			B ₁	L ₁	J ₁	K	T	Oil hole			Width W ₁	Height H ₁	B ₂
							B	J	M×Pitch×ℓ						Hole diameter	T ₁	N			
PE05AR	—	6.5	1.4	3.5	17	24.1	13	—	M2.5×0.45×1.5	2.0	16.4	8.2	5.1	2.5	Ø0.9	1.3	—	10	4.0	—
PE07TR	—	9.0	2.0	5.5	25	31.1	19	10	M3×0.5×2.8	3.0	20.8	5.4	7.0	3.0	Ø1.9	1.9	—	14	5.2	—
PE09TR	■	12.0	4.0	6.0	30	39.8	21	12	M3×0.5×3	4.5	26.6	7.3	8.0	2.8	Ø2.0	2.3	—	18	7.5	—
PE09UR	■	12.0	4.0	6.0	30	51.2	23	24	M3×0.5×3	3.5	38.0	7.0	8.0	2.8	Ø2.0	2.3	—	18	7.5	—
PE12AR	■	14.0	4.0	8.0	40	45.0	28	15	M3×0.5×4	6.0	31.0	8.0	10.0	3.2	Ø2.5	2.7	—	24	8.5	—
PE12BR	■	14.0	4.0	8.0	40	60.0	28	28	M3×0.5×4	6.0	46.0	9.0	10.0	3.2	Ø2.5	2.7	—	24	8.5	—
PE15AR	■	16.0	4.0	9.0	60	56.6	45	20	M4×0.7×4.5	7.5	38.4	9.2	12.0	4.1	Ø3.0 (°3)	3.2	(3.3)	42	9.5	23
PE15BR	■	16.0	4.0	9.0	60	76.0	45	35	M4×0.7×4.5	7.5	57.8	11.4	12.0	4.1	Ø3.0 (°3)	3.2	(3.3)	42	9.5	23

■: Interchangeable type is available.

(°3) Drive-In grease fitting for Ø3 is available to PE15.

(4) Basic dynamic load rating is a load that allows for a 50-km rating fatigue life and is a vertical and constant load on the ball slide mounting surface. To convert C to C₁₀₀ for a 100-km rating fatigue life, divide C by 1.26.

Please refer to Table 14 for each dimension.




Fig. 8 Assembly (PE Series)

Unit: mm

Rail				Basic Load rating (°2)							Ball diameter	Weight	
Mounting bolt hole	B ₃	G	Maximum length	Dynamic	Static	Static moment (N·m)				Ball slide		Rail	
				C (N)	C ₀ (N)	M _{RO}	M _{PO}		M _{YO}				
d×D×h		(Reference)	L _{0max}				one slide	two slides in close contact	one slide	two slides in close contact	D _w	(g)	(g/100 mm)
2.3×3.3×0.8	2.5	5.0	210	520	775	2.06	1.28	9.90	1.28	9.90	1.0000	4	11
2.4×4.2×2.3	3.5	5.0	375	1 090	1 370	5.20	2.70	21.80	2.70	21.8	1.5875	8	23
3.5×6×4.5	4.5	7.5	600	1 490	2 150	9.90	6.10	41.00	6.10	41.0	1.5875	16	35
				2 100	3 500	16.20	15.60	88.00	15.60	88.0		25	
3.5×6×4.5	6.0	10.0	800	2 830	3 500	21.10	11.40	73.50	11.40	73.5	2.3812	32	65
				4 000	5 700	34.50	28.30	174.00	28.30	174.0		53	
3.5×6×4.5	7.5	15.0	1 000	5 550	6 600	49.50	25.60	190.00	25.60	190.0	3.1750	59	105
				8 100	11 300	84.50	69.50	435.00	69.50	435.0		100	

To fix rails of PU05TR, use M2 × 0.4 cross-recessed pan head machine screw for precision instrument.
(JIS 10-70 No. 0 pan head machine screw No. 1) (JIS: Japanese Camera Industrial Standard)

Unit: mm

Rail					Basic load rating (°4)							Ball diameter	Weight	
Pitch	Mounting bolt hole	B ₃	G	Maximum length	Dynamic	Static	Static moment (N·m)				Ball slide		Rail	
							C	C ₀	M _{RO}	M _{PO}				M _{YO}
F	d×D×h		(Reference)	L _{0max}	C (N)	C ₀ (N)	M _{RO}	one slide	two slides in close contact	one slide	two slides in close contact	D _w	(g)	(g/100 mm)
20	3×5×1.6	5.0	7.5	150	690	1 160	6.0	2.75	17.5	2.75	17.5	1.0000	7	34
30	3.5×6×3.2	7.0	10.0	600	1 580	2 350	16.7	7.20	46.0	7.20	46.0	1.5875	19	55
30	3.5×6×4.5	9.0	10.0	800	3 000	4 500	36.5	17.3	113.0	17.3	113.0	2.0000	35	95
					4 000	6 700	54.5	37.5	210.0	37.5	210.0		50	
40	4.5×8×4.5	12.0	15.0	1 000	4 350	6 350	70.5	29.3	180.0	29.3	180.0	2.3812	66	140
					5 800	9 550	106.0	63.5	345.0	63.5	345.0		98	
40	4.5×8×4.5	9.5	15.0	1 200	7 600	10 400	207.0	59.0	370.0	59.0	370.0	3.1750	140	275
					10 300	16 000	320.0	135.0	740.0	135.0	740.0		211	

To fix rails of PE05AR, use M2.5 × 0.45 cross-recessed pan head machine screw for precision instrument.
(JIS 10-70 No. 0 pan head machine screw No. 3) (JIS: Japanese Camera Industrial Standard)

INTERCHANGEABLE TYPE

BALL SLIDE OF INTERCHANGEABLE TYPES

Please refer to Table 13 for each dimension.




Fig. 9 Ball slide of interchangeable types (PU Series)

Please refer to Table 14 for each dimension.




Fig. 10 Ball slide of interchangeable types (PE Series)

RAIL OF INTERCHANGEABLE TYPES

Please refer to Table 13 for each dimension.




Fig. 11 Rail of interchangeable types (PU Series)

Please refer to Table 14 for each dimension.




Fig. 12 Rail of interchangeable types (PE Series)

INTERCHANGEABILITY WITH LU SERIES/LE SERIES

The PU series/PE series is designed to be interchangeable* with the LU series/LE series for its mounting dimensions and load ratings.

Refer to Figs. 7, 8 and Tables 13, 14 for more details.

(*) Load ratings for PU05 and PE05 are not interchangeable

HANDLING PRECAUTIONS

- › NSK Linear Guides may become damaged when struck or hit.
- › Maximum operating temperature must be 80°C or below. Exceeding this limit may damage resin parts.
- › Maximum operating temperature must be 50°C (max. momentary 80°C) when attaching NSK K1™. Also, avoid exposure to organic solvents with a degreasing effect. Do not immerse in kerosene or rust preventative oil (with kerosene ingredients).
- › Handling of interchangeable types
 - Interchangeable ball slide will be delivered on a provisional rail (installing fixture).
 - Be sure to use the provisional rail when mounting ball slide(s) on to a rail.
 - Do not remove the ball slide from provisional rail until sliding on to a rail.



NSK AMERICAS

Argentina

NSK Argentina SRL
Buenos Aires
54.11.4762.6556

Brazil

NSK Brasil Ltda.
Sao Paulo SP
55.11.3269.4700

Canada

NSK Canada Inc.
Mississauga ON
1.877.994.6675

Latin America

NSK Latin America Inc.
Miami FL
1.305.477.0605

Mexico

NSK Rodamientos Mexicana, S.A. de C.V.
Tlalnepantla de Baz MX
52.55.3682.2900

United States

NSK Corporation
Ann Arbor MI
1.888.446.5675

Website: www.nskamericas.com

NSK Global: www.nsk.com

Every care has been taken to ensure the accuracy of the data contained in this brochure, but no liability can be accepted for any loss or damage suffered through errors or omissions.

Printed in the USA ©NSK 2018. The contents of this publication are the copyright of the publishers.